



NEROLAC BEAUTY LITTLE MASTER SHEEN INTERIOR EMULSION

PRODUCT DESCRIPTION

Nerolac Beauty Little Master Sheen is an Economy Interior Wall Emulsion with very good sheen, smoothness, coverage & durability.

PERFORMANCE FEATURES & BENEFITS

	Rich Sheen		Excellent Whiteness
	Brighter Finish		Good Ease of Application
	Good Coverage		Excellent Washability
	Good Durability		Low VOC
	Excellent Flow and Levelling		

SURFACE PREPARATION

1. Ensure the surface is clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using suitable abrasive paper and thereafter wipe off.
2. Treat fungus affected areas with Nerolac Fungicidal Solution and allow it to react for 6-8 h.
3. Apply a coat of suitable Primer** followed by Nerolac Wall Putty### to level the dents & make the surface uniform. Sand the surface with emery paper no. 180 and wipe clean.
4. Apply 2 coats Nerolac Acrylic Wall Putty or Nerolac Cement Putty to level the dents, dry, followed by sanding with emery paper 180 or 220 wipe clean.
5. Again, apply a coat of suitable primer**, Sand the surface with emery paper no. 320 and wipe.
6. Then apply two to three coats of Nerolac Beauty Little Master Sheen Interior Emulsion.

RECOMMENDED SYSTEM FOR APPLICATION

1. Primer**(1 coat), Dry# in 4-6 h.
2. Putty##, Dry in 6-8 h.
3. Primer**(1 coat), Dry# in 4-6 h.
4. Finish Nerolac Beauty Little Master Sheen Interior Emulsion (2-3 coats), Dry min. 4-6 h in between coats.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces skip steps 1 & 2 and start with step 3

Sand the surface with Emery paper and clean before application of subsequent coat.

**Nerolac Premium Primer (Water Thinnable / Solvent Thinnable) or Nerolac Popular Primer (Water Thinnable / Solvent Thinnable).

##Nerolac Wall putty or Nerolac Cement putty. #Minimum 8 h for solvent Thinnable primer & minimum 4-6 h for water Thinnable Primer.

PRECAUTIONS

1. Refer MSDS for "Nerolac Beauty Little Master Sheen" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection will cause danger. In either case, move to fresh air & consult medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h. of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face mask.

TECHNICAL DATA



Roller Note: Actual coverage may vary depending on method & condition of application, surface roughness & surface

POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with mild soap solution and wipe clean. Please allow 2 weeks of drying time to freshly painted wall for it to be ready for stain removal/cleaning.



SAFETY FEATURES

Non-Flammable



PACK SIZE

1 L, 4 L, 10 L & 20 L



SHELF LIFE

2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat



SHADE RANGE

11000+ Shades

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our experience with the type of products. Therefore, actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products. The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects, or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.