



## NEROLAC IMPRESSIONS KASHMIR



### PRODUCT DESCRIPTION

Nerolac Impressions Kashmir Luxury Emulsion is a superior quality 100% acrylic emulsion based interior wall paint with germ killing formula. It is based on Silver Ion Technology that kills 99% of bacteria on the painted surface and gives safe & healthy environment at home. It gives your walls a radiant sheen and a rich smooth finish along with ultra-low odour. The opacity, washability, stain resistance and levelling are outstanding, thereby creating a high class finish that keeps the wall awe-inspiring for years.

### PERFORMANCE FEATURES & BENEFITS



### SURFACE PREPARATION

1. Rub the surface using a suitable abrasive paper and wipe it off to ensure that the surface is clean, dry and free from dirt, grease, wax or any other defective or poorly adhering material.
2. Treat fungus affected areas with Nerolac Fungicidal Solution and allow it to react for 6-8 H
3. Apply 1 coat of Nerolac Perma Damp Protect Interior at 50% dilution. (OR) Self-Priming at 100% dilution.
4. Sand the surface with emery paper no. 320 and clean the surface with cloth.
5. Apply 1 coat of Nerolac Perma Damp Protect Interior at 50% dilution. (OR) Self-Priming at 100% dilution.
6. Sand the surface with Emery paper no.320 and clean the surface with cloth before painting.
7. Finally, apply 2-3 coats of Nerolac Impressions Kashmir at 40-50% dilution. Dark shade may require additional coat for hiding.

### RECOMMENDED USAGE

Nerolac Impressions Kashmir Luxury Emulsion is designed for application on new as well as previously painted interior surfaces such as plaster, brickwork, cement rendering, concrete, hard boards, etc.

### APPLICATION (FOR NEW MASONRY SURFACES)

1. Primer\*\* (1 coat), Dry for 4-6 h
2. Putty##, Dry for 6-8 h
3. Primer\*\* (1 coat), Dry for 4-6 h
4. Finish Nerolac Impressions Kashmir (2-3 coats). Dry min for 3-4 h in between coats.

Sand the surface with Emery paper and clean before application of subsequent coat.

\*\* Nerolac Perma Damp Protect Interior at 50% dilution. (OR) Self-Priming at 100% dilution.

##Nerolac Wall putty or Nerolac Cement putty.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces, skip steps 1 & 2 and start with step 3.

### PRECAUTIONS

1. Refer MSDS for "Nerolac Impressions Kashmir" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection will cause danger. In either case, move to fresh air & consult medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face mask.

## TECHNICAL DATA



\*\*\* Actual coverage may vary depending on method & condition of application, surface roughness & surface.

## POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with mild soap solution and wipe clean. Please allow 2 week of drying time to freshly painted wall for it to be ready for stain removal/cleaning.



### SAFETY FEATURES

Non-Flammable



### SHADE RANGE

As per Nerolac Colour Scapes Fandeck & Shade Card



### PACK SIZE

1 L., 4 L., 10 L. & 20 L.



### SHELF LIFE

2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat.

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.