



## NEROLAC IMPRESSIONS IDEAZ DESIGNER FINISH

# NEROLAC

Colours that Care



### PRODUCT DESCRIPTION

Nerolac Impressions Ideaz Designer Finish is a Special Effect Designer series range that creates a variety of designs on interior walls in matt finish.

### PERFORMANCE FEATURES & BENEFITS

	Creation of Various Designs with Different Application Tools		Excellent Stain Resistance
	Excellent Fungal Resistance		Soft Sheen
	Excellent Workability		Washable

### SURFACE PREPARATION

1. Rub the surface using a suitable abrasive paper and wipe it off to ensure that the surface is clean, dry and free from dirt, grease, wax or any other defective or poorly adhering material.
2. Treat fungus affected areas using Nerolac Fungicidal Solution and allow it to react for 6-8 h.
3. Apply a coat of suitable Primer\*\* ( water / solvent thinnable ) followed by Putty### (wherever required) to level and smoothen the surface.
4. Sand the surface with emery paper 180 & wipe clean.
5. Apply another coat of suitable primer\*\* on puttied areas.
6. Sand the surface with emery paper 320 & clean the surface with cloth before painting.
7. Finally, apply two to three coats of Nerolac Impressions HD as per recommended thinning. Dark shades may require additional coat for hiding.

### RECOMMENDED USAGE

Nerolac Impressions Ideaz Designer Finish can be applied on the interior surfaces such as smooth plaster, brickwork, cement rendering, concrete, hardboard, building boards, etc.

### RECOMMENDED SYSTEM FOR APPLICATION - For New Masonry Surfaces

1. Primer\*\* (1 coat), Dry# in 4-6 h.
2. Putty###, Dry in 6-8 h.
3. Primer\*\* (1 coat), Dry# in 4-6 h.
4. Base Coat (2-3 coats) Impressions HD, Dry in 4-6 h in between the coats.
5. Finish Coat (1 Coat) Nerolac Impressions Ideaz (as per design required)

Sand the surface with Emery paper and wipe clean before application of subsequent coat.

\*\*Nerolac Premium Primer (Water Thinnable / Solvent Thinnable) or Nerolac Popular Primer (Water Thinnable / Solvent Thinnable).

###Nerolac Wall Putty or Nerolac Cement Putty.

#Minimum 8 h for Solvent Thinnable Primer & minimum 4-6 h for Water Thinnable Primer.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces skip steps 1 & 2 and start with step 3.

### PRECAUTIONS

1. Refer MSDS for "Nerolac Ideaz Designer Finish" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection is dangerous. In either case, move to fresh air & consult a medical practitioner.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. The container must be tightly closed when not in use. Stir well before use.
9. Use safety equipment like rubber or polythene gloves, safety goggles / glasses & face mask.

## TECHNICAL DATA



\*\* Actual Covering capacity may vary depending upon the method of application & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity & shade.

## POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 2 weeks before cleaning.

	<b>SAFETY FEATURES</b> Non-Flammable		<b>PACK SIZE</b> 200 ml, 1 L
	<b>SHADE RANGE</b> As per Shade Card		<b>SHELF LIFE</b> 2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat
	<b>NO. OF SHADES POSSIBLE</b> More Than 70		

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.